## **COMPLETE ENTRANCE QUOTE**

360-862-8328 | www.liftsolutions.net

LIFT SOLUTIONS

*Company:	*Job Name:		
Address:	*Location:		*Location State:
	*Elevator #:		Building:
*Contact Person: *Floors:			
Phone: *Email:			
Quote Needed By:	Estimated Ship Date:		
Original Manufacturer:	ANSI Code Year A17.1-		
*DOOR TYPE - (1 1/4 in Thick Panels) *QUANTITY	НА	ANDING	
Two Speed Center Opening- 2CO Single Speed Side Opening - 1SO TRAVEL	rs:	Left	Right Center
*OPENING WIDTH       *OPENING HEIGHT       *OPERATOR TYPE       SIL         36 in       84 in       GAL Standard	L CONSTRUCTION       *SILL FINISH         PSD Standard Groutless       Extruded Aluminum         PSD Groutless with Gussets       Extruded Stainless Steel         PSD Groutless with Angle       Nickel Silver         Angle by Others/Pocket 3in - 6in       Stainless Steel         Angle by Others Pocket 3in MAX       Bronze		
*HOISTWAY WALL       Prime Painted Grey Matte (         Thickness (inches)       Painted(RAL)         Masonry (Block)       Stainless, 304 #4 (Satin)         Drywall       Stainless, 316 #4 (Satin)         *FRAME TYPE       Stainless, 304 #8 Mirror         Bolted Knock-Down       Bronze Muntz, #8 Mirror         Welded       Bronze Muntz, Light Oxidiz         Galvanized       Vortex, Non Directional	Rimex) e		

### STANDARD CONSTRUCTION SPECIFICATIONS

1. Passenger Entrances are 1-1/2 hour fire rated UL labeled

- 2. Door Panels 16 Gauge Face Sheet, 16 Gauge Back Sheet
- 3. Two Door Guides and one 14 gauge safety retainer per panel
- 4. Standard GAL equipment mounting provisions are included
- 5. Frames: 14 Gauge Sheet with a 2" square profile (bolted, welded, or welded and mitered)
- 6. Fascia: 16 Gauge Sheet with maximum 12 ft floor height maximum (blind fascia for skipped or bypassed floors are non-standard)
- 7. Standard Header and Strut Design: 12 Gauge including Hoistway Material (header, struts, etc.)
- 8. Sill Construction: Aluminum (standard), Nickel Silver, Stainless Steel or Bronze are optional

# **Replacement Panels**

QUANTITY APPROVAL DRAWING REQUIRED?	
Landing Doors Car Doors _	Yes No
DOOR TYPE - (1 1/4 in Thick Panels)         Single Speed Center Opening - 1CO         Two Speed Center Opening - 2CO         Single Speed Side Opening - 1SO         Two Speed Side Opening - 2SO         Three Speed Side Opening - 3SO         DOOR FINISH         Prime Painted Grey Matte (RAL 7044)         Painted (RAL )         Stainless, 304 #4 (Satin)         Stainless, 316 #4 (Satin)         Stainless, 5WL Rigidized (RIMEX)         Stainless, Blackened	HANDING Left Right Center Ce
Stainless, 304 #8 Mirror     OPENING WIDTH        36 in   42 in   96 in   48 in   54 in   0ther     0ther     PANEL WIDTH (in)     PANEL WIDTH (in)     PANEL WIDTH (in)	PANEL THICKNESS   1 1/4 in   1 1/2 in   2 3/4 in   1 in (Car Only)   OPERATOR TYPE   GAL Standard   Other   Herein Control Control   Looking FROM HALLWAY   Left   ONLY REQUIRED FOR   ONLY REQUIRED FOR CENTER OPENING DOORS

### Door Panel Kit Includes:

Nylon Gibs, Safety Retainer, Sight Guard, Escutcheon & Neoprene Astragal for Center Opening Doors 1 1/2 HR UL Labels (landing doors only) where allowed

#### Material Not Included:

Access Switch, Braille Plates, Painted/Applied Floor Designations

#### **Panel Construction**

16 GA front sheet & back sheet Reinforced Panel drilled per operator template

Entrances Additional Information: \_\_\_\_\_

Replacement Panels Additional Information: \_\_\_\_\_